

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

FLOORMATE

Floormate provides excellent moisture protection and is ideal for areas with heavy foot traffic. Made from high performance recycled crumb rubber, it incorporates a foil vapour barrier to prevent migration of moisture from the subfloor. The product combines comfort and support with great sound and thermal insulation.

The rubber crumb is made up of recycled car tyres, making Floormate an incredibly sustainable and environmentally friendly option.



TECHNICAL DATA

MATERIAL	Recycled crumb rubber
COLOUR	Black
THICKNESS	3.5mm
WIDTH	13kg
COVERAGE	10m ²
TOG RATING	0.8
IMPACT SOUND REDUCTION	23dB
TENSILE STRENGTH (LENGTHWISE)	186N
TENSILE STRENGTH (CROSSWISE)	131N
UNDERFLOOR HEATING	Yes
MOISTURE BARRIER	Yes
THICKNESS LOSS, DYNAMIC LOADING BS4098	10%
THICKNESS LOSS, STATIC LOADING BS4052	10%
FLAMMABILITY, RADIUS OF EFFECTS OF IGNITION BS4709	Low

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK