

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA & APPLICATION

# IIP SURFACE PRIMER

Woodpecker IIP Surface Primer is a high performance, solvent-free, water-borne surface primer used to seal porous substrates in preparation for Woodpecker MS Parquet Adhesive or WP50 Adhesive Sausages. IIP is suitable for use with highly absorbent mineral subfloors such as cement bound, concrete, calcium-sulphate bound (anhydrite) and levelled subfloors. For indoor use only.



## TECHNICAL DATA

MATERIAL	Synthetic dispersion mixture
COLOUR	Green
CURING SYSTEM	Physical drying
CONSISTENCY	Liquid
DRYING TIME AT	
70°F AND 50% RH	30 minutes - cementitious subfloors 60 minutes - subfloors with limited porosity 4 hours - wooden and chipboard subfloors 12 hours - non-absorbing surfaces 24 hours - anhydrite subfloors
TEMPERATURE RESISTANCE	32°F to 120°F
UNDERFLOOR HEATING	Yes
TOTAL SOLIDS CONTENT	Approx 20%
APPLICATION RATE	5 - 10 ml / ft <sup>2</sup>

## DIRECTIONS FOR USE:

- Shake/stir thoroughly before use
- Apply undiluted using brush/roller

## INSTALLATION DATA

Drying time approx. 20 - 30 minutes

## CONSUMPTION:

Approximate coverage: 100 ft<sup>2</sup>/Liter

## SUBFLOOR:

The subfloor must be even, dry (<75%RH), clean, smooth, sound and free from cracks. Residues such as old adhesive, oil and stains may act negatively on the adhesion strength. The temperature of the surface must be above 40°F when the primer is applied to the subfloor and underfloor heating must be off for at least 48 hours before, during and after application.

## APPLICATION:

Vacuum the subfloor before application. Shake/stir thoroughly before use. Apply the primer using a brush or roller. Use undiluted on non-absorbent surfaces and diluted with 1 part water to 4 parts primer for absorbent surfaces. Wash tools with warm water immediately after use.

## STORAGE:

Shelf life of 12 months at 40°-85°F

## SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK