

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET GOODRICH FEATHER OAK

PRODUCT DETAILS

| | |
|--------------------------|-------------------------------|
| PRODUCT CODE | 32-OGW-001 |
| CONSTRUCTION | Engineered Wood |
| SPECIES | Oak |
| WEAR LAYER | 4mm |
| BACKING | Eucalyptus Ply |
| THICKNESS | 15mm |
| WIDTH | 90mm |
| LENGTH | 400mm |
| PACK SIZE | 1.296m ² |
| PLANKS PER PACK | 36 |
| GRADE | Rustic |
| FINISH | Brushed & Matt Lacquered |
| JOINT TYPE | Tongue & Groove |
| BEVELLED EDGES | All 4 Edges |
| FIXING METHOD | Floated, nailed or stuck down |
| UNDERFLOOR HEATING | Suitable if stuck down |
| TOG RATING | 1.13 |



TECHNICAL CRITERIA

| | |
|----------------------------------|--------------------|
| ORIGIN | Europe |
| RESPONSIBLE CERTIFICATION | FSC |
| JANKA HARDNESS RATING | 1,360 lbf (6,000N) |
| FORMALDEHYDE EMISSION | E1 |
| PENTACHLOROPHENOL EMISSION | Undetected |
| REACTION TO FIRE | Dfl s1 |
| THERMAL CONDUCTIVITY | 0.143 W / mK |

GRADING CRITERIA

| | |
|-----------------------------------|-------------|
| MAXIMUM SIZE OF SOUND KNOTS | 50mm |
| MAXIMUM SIZE OF DEAD KNOTS | 30mm |
| HEARTWOOD | Allowed |
| SAPWOOD | Allowed |
| INSECT HOLES | Not Allowed |
| FILLER | Allowed |
| COLOUR VARIATION | Allowed |
| SMALL CRACKS | Allowed |
| ROT | Not Allowed |

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK

