

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA SHEET GOODRICH SALTED OAK

### PRODUCT DETAILS

PRODUCT CODE .....	32-SGR-001
CONSTRUCTION .....	Engineered Wood
SPECIES .....	Oak
WEAR LAYER .....	4mm
BACKING .....	Eucalyptus Ply
THICKNESS .....	15mm
WIDTH .....	90mm
LENGTH .....	400mm
PACK SIZE .....	1.296m <sup>2</sup>
PLANKS PER PACK .....	36
GRADE .....	Rustic
FINISH .....	Brushed & Matt Lacquered
JOINT TYPE .....	Tongue & Groove
BEVELLED EDGES .....	All 4 Edges
FIXING METHOD .....	Floated, nailed or stuck down
UNDERFLOOR HEATING .....	Suitable if stuck down
TOG RATING .....	1.13



### TECHNICAL CRITERIA

ORIGIN .....	Europe
RESPONSIBLE CERTIFICATION .....	FSC
JANKA HARDNESS RATING .....	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION .....	E1
PENTACHLOROPHENOL EMISSION .....	Undetected
REACTION TO FIRE .....	Dfl s1
THERMAL CONDUCTIVITY .....	0.143 W / mK

### GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS .....	50mm
MAXIMUM SIZE OF DEAD KNOTS .....	30mm
HEARTWOOD .....	Allowed
SAPWOOD .....	Allowed
INSECT HOLES .....	Not Allowed
FILLER .....	Allowed
COLOUR VARIATION .....	Allowed
SMALL CRACKS .....	Allowed
ROT .....	Not Allowed

### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK

