WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET BERKELEY CELLAR OAK

PRODUCT DETAILS PRODUCT CODE 38-BCO-001 CONSTRUCTION Engineered Wood SPECIES Oak WEAR LAYER 4mm BACKING Eucalyptus Ply THICKNESS 15mm LENGTH 1860mm Packs include cut lengths PACK SIZE 2.11m² PLANKS PER PACK 6 GRADE Extra Rustic FINISH Oiled JOINT TYPE Tongue & Groove BEVELLED EDGES All 4 Edges UNDERFLOOR HEATING Suitable if stuck down

GRADING CRITERIA	
MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed



TECHNICAL CRITERIA
ORIGINEurope
RESPONSIBLE CERTIFICATION FSC
JANKA HARDNESS RATING
FORMALDEHYDE EMISSIONEI
PENTACHLOROPHENOL EMISSIONUndetected
REACTION TO FIRE
THERMAL CONDUCTIVITY

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR **T**: 02920 888 223 **F**: 02920 881 694 info@woodpeckerflooring.co.uk



