

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA SHEET HARLECH SELECT OAK OILED

### PRODUCT DETAILS

PRODUCT CODE .....	35-H00-005
CONSTRUCTION .....	Engineered Wood
SPECIES .....	Oak
WEAR LAYER .....	4mm Oak
BACKING .....	Poplar
THICKNESS .....	15mm
WIDTH .....	190mm
LENGTH .....	1900mm
PACK SIZE .....	2.166m <sup>2</sup>
PLANKS PER PACK .....	6
PACKS PER PALLET .....	60
GRADE .....	Select
FINISH .....	Oiled
JOINT TYPE .....	Tongue & Groove
BEVELLED EDGES .....	All 4 Edges
FIXING METHOD .....	Floated, nailed or stuck down
UNDERFLOOR HEATING .....	Suitable if fully stuck down
TOG RATING .....	1.13



### TECHNICAL CRITERIA

ORIGIN .....	Europe
RESPONSIBLE CERTIFICATION .....	FSC
JANKA HARDNESS RATING .....	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION .....	E1
PENTACHLOROPHENOL EMISSION .....	ND
REACTION TO FIRE .....	Dfl s1
THERMAL CONDUCTIVITY .....	0.143 W / mK

### GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS .....	20mm
MAXIMUM SIZE OF DEAD KNOTS .....	10mm
HEARTWOOD .....	Not Allowed
SAPWOOD .....	10%
INSECT HOLES .....	Not Allowed
FILLER .....	Allowed
COLOUR VARIATION .....	Limited
SMALL CRACKS .....	Not Allowed
ROT .....	Not Allowed

### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



The mark of  
responsible forestry

25  
YEARS  
WARRANTY

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA SHEET HARLECH SELECT OAK LACQUERED

### PRODUCT DETAILS

PRODUCT CODE	35-HOL-001
CONSTRUCTION	Engineered Wood
SPECIES	Oak
WEAR LAYER	4mm Oak
BACKING	Poplar
THICKNESS	15mm
WIDTH	190mm
LENGTH	1900mm
PACK SIZE	2.166m <sup>2</sup>
PLANKS PER PACK	6
PACKS PER PALLET	60
GRADE	Select
FINISH	Matt Lacquered
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if fully stuck down
TOG RATING	1.13



### TECHNICAL CRITERIA

ORIGIN	Europe
RESPONSIBLE CERTIFICATION	FSC
JANKA HARDNESS RATING	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION	E1
PENTACHLOROPHENOL EMISSION	ND
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY	0.143 W / mK

### GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	20mm
MAXIMUM SIZE OF DEAD KNOTS	10mm
HEARTWOOD	Not Allowed
SAPWOOD	10%
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Limited
SMALL CRACKS	Not Allowed
ROT	Not Allowed

### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



The mark of  
responsible forestry

25  
YEARS  
WARRANTY