

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET YORK ANTIQUE OAK

PRODUCT DETAILS

PRODUCT CODE	36-YOA-150
CONSTRUCTION	Solid Wood
SPECIES	Oak
THICKNESS	18mm
WIDTH	150mm
LENGTH	300-1600mm
PACK SIZE	1.98m ²
PLANKS PER PACK	Variable
PACKS PER PALLET	52
GRADE	Rustic
FINISH	Matt Lacquered
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Stick down or secret nail
UNDERFLOOR HEATING	Not advised



GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed

TECHNICAL CRITERIA

ORIGIN	Europe
RESPONSIBLE CERTIFICATION	FSC
JANKA HARDNESS RATING	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION	E1
PENTACHLOROPHENOL EMISSION	ND
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY	0.143 W / mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



The mark of
responsible forestry

25
YEARS
WARRANTY