

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET SALCOMBE NATURAL OAK

PRODUCT DETAILS

PRODUCT CODE	45-WGO-000
CONSTRUCTION	Engineered Wood
SPECIES	Oak
WEAR LAYER	3mm Oak
BACKING	Poplar
THICKNESS	14mm
WIDTH	190mm
LENGTH	1900mm
PACK SIZE	2.888m ²
PLANKS PER PACK	8
PACKS PER PALLET	40
GRADE	Rustic
FINISH	Brushed & Matt Lacquered (UV cured)
JOINT TYPE	Easiloc
END JOINT TYPE	2G
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated
UNDERFLOOR HEATING	Suitable
TOG RATING	1.13



TECHNICAL CRITERIA

ORIGIN	Europe
RESPONSIBLE CERTIFICATION	FSC
JANKA HARDNESS RATING	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION	E1
PENTACHLOROPHENOL EMISSION	ND
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY	0.143 W / mK

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	50mm
MAXIMUM SIZE OF DEAD KNOTS	30mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



The mark of
responsible forestry

25
YEARS
WARRANTY