


# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA SHEET LYNTON WEALD OAK STRATEX


### PRODUCT DETAILS

PRODUCT CODE	33-LYT-002
CONSTRUCTION	Natural mineral / resin composite
WEAR LAYER	1.0mm real wood veneer
BACKING	Crosslinked microcellular foam
THICKNESS	7mm
WIDTH	165mm
LENGTH	1220mm
PACK SIZE	2.01m <sup>2</sup>
PLANKS PER PACK	10
PACKS PER PALLET	42
FINISH	Brushed and matt lacquered
JOINT TYPE	Easiloc
END JOINT TYPE	2G
BEVELLED EDGES	Micro-bevel on 4 sides
FIXING METHOD	Floating
UNDERFLOOR HEATING	Suitable
MOISTURE BARRIER	Not required
PERIMETER EXPANSION GAP	2-3mm
SUBFLOOR TOLERANCE	< 2mm



### TECHNICAL CRITERIA

FORMALDEHYDE EMISSION	E1
PENTACHLOROPHENOL EMISSION	Undetected
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY	Not Tested (NR)
DIMENSIONAL STABILITY	0.08%
SHRINKAGE RATE 5-35c	0.01%
IMPACT SOUND REDUCTION	16dB



### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK

25  
YEARS  
WARRANTY