

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA SHEET HARLECH WHITE SMOKED OAK 150

### PRODUCT DETAILS

PRODUCT CODE .....	35-HWS-001
CONSTRUCTION .....	Engineered Wood
SPECIES .....	Oak
WEAR LAYER .....	4mm Oak
BACKING .....	Poplar
THICKNESS .....	15mm
WIDTH .....	150mm
LENGTH .....	1900mm
PACK SIZE .....	1.71m <sup>2</sup>
PLANKS PER PACK .....	4
PACKS PER PALLET .....	60
GRADE .....	Rustic
FINISH .....	Brushed & Matt Lacquered
JOINT TYPE .....	Tongue & Groove
BEVELLED EDGES .....	All 4 Edges
FIXING METHOD .....	Floated, nailed or stuck down
UNDERFLOOR HEATING .....	Suitable if fully stuck down
TOG RATING .....	1.13



### TECHNICAL CRITERIA

ORIGIN .....	Europe
RESPONSIBLE CERTIFICATION .....	FSC
JANKA HARDNESS RATING .....	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION .....	E1
PENTACHLOROPHENOL EMISSION .....	ND
REACTION TO FIRE .....	Dfl s1
THERMAL CONDUCTIVITY .....	0.143 W / mK

### GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS .....	50mm
MAXIMUM SIZE OF DEAD KNOTS .....	30mm
HEARTWOOD .....	Allowed
SAPWOOD .....	Allowed
INSECT HOLES .....	Not Allowed
FILLER .....	Allowed
COLOUR VARIATION .....	Allowed
SMALL CRACKS .....	Allowed
ROT .....	Not Allowed

### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



The mark of  
responsible forestry

25  
YEARS  
WARRANTY