

## Uni2 Maxi

**Dimensions:** 21 x 190 x 1900mm

**Top layer:** 6mm Oak

**Core:** Plywood

**Pack size:** 2.17m<sup>2</sup>

**Joint:** Tongue + Groove.

**Type:** Engineered

**Bevels:** Micro bevel 4 edges

**Lacquer/Oil:** 5 UV oil.

**Certification:** FSC

**UFH:** Suitable if fully stuck down.

**Warranty:** 10 years

### Methods of Installation

- Floated on a suitable underlay. Recommended Woodpecker Aquastop. Glue the joint with a Flooring grade PVA.
- This product should be stuck down when used with UFH with a flexible flooring adhesive such as the Woodpecker MS Parquet adhesive. Spread with 3mm or 5mm notched trowel with a minimum of 80% adhesion.
- Secret nailed. Nailed every 300mm. Recommend the Powernail.

We recommend when ordering this product that 5% or 10% waste is allowed for. If the room is relatively straightforward 5%. If the room has alcoves, fireplace, bay windows, etc 10%.

The answers to commonly asked questions:

- Acclimatisation should be carried out with the product in its packaging. The packaging should not be opened.
- Acclimatisation needs to be a two or three days. When installing over UFH the product needs to be acclimatised with the heating running for at least 10 days. The heating should be switched off, left to cool before installation. The heating must then be switch back on at a low temperature and raised 1 degree per day until the desired temperature is reached. The UFH should be running constantly on the thermostat which will keep the room temperature constant. For further information please refer to page 164 in the Woodpecker catalogue.
- The planks are sometimes prone to bowing end to end. This is normal to a certain extent. Two different products bonded together reacting at different speeds to moisture do create this. After a period of time or shortly after installation it will disappear. There is a

tolerance of approximately 30mm. This is the measurement between the floor and the middle of the plank when both ends are on a flat subfloor.

- Suitable for use in domestic and commercial applications. Suitable for use in any room but may react to moisture so not recommended in a bathroom. Wood and moisture are natural enemies so it can only be installed where the humidity is constant.

**SPECIFICATION DISCLAIMER** This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR  
T: 02920 888 223 F: 02920 881 694 [info@woodpeckerflooring.co.uk](mailto:info@woodpeckerflooring.co.uk)

[WWW.WOODPECKERFLOORING.CO.UK](http://WWW.WOODPECKERFLOORING.CO.UK)

