

WOODPECKER TRADE

TECHNICAL DATA SHEET ENDURA OAK

PRODUCT DETAILS

PRODUCT CODE	83-HOZ-001
CONSTRUCTION.....	Engineered
SPECIES	Oak
WEAR LAYER	3mm Oak
BACKING	Poplar
THICKNESS.....	14mm
WIDTH.....	150mm
LENGTH	1900mm
PACK SIZE.....	1.71m ²
PLANKS PER PACK.....	6
GRADE	Rustic
PACKS PER PALLET.....	77
FINISH	Oiled (UV cured)
JOINT TYPE.....	T&G
END JOINT TYPE.....	T&G
BEVELLED EDGES	Micro bevel, all 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable
TOG RATING.....	1.13



TECHNICAL CRITERIA

ORIGIN.....	Europe
RESPONSIBLE CERTIFICATION	FSC(R)
JANKA HARDNESS RATING.....	1,360 lbf (6000N)
FORMALDEHYDE EMISSION.....	E1
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY.....	0.143 W/mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 **F:** 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



The mark of
responsible forestry

