

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET DESIGN PANELS MULTI BEVEL

PRODUCT DETAILS

CONSTRUCTION.....	Engineered Wood
SPECIES.....	Oak
WEAR LAYER.....	4mm Oak
BACKING.....	Birch Ply
THICKNESS.....	15mm
WIDTH.....	750mm
LENGTH.....	750mm
PACK SIZE.....	0.56m ²
PLANKS PER PACK.....	1
PLANKS PER PALLET.....	N/A
GRADE.....	Rustic
FINISH.....	Hardwax oil
JOINT TYPE.....	Tongue & Groove
BEVELLED EDGES.....	All joints
FIXING METHOD.....	Stuck down
UNDERFLOOR HEATING.....	Suitable if fully stuck down
TOG RATING.....	1.13



AVAILABLE IN LIMED OAK | ROYAL OAK | AGED OAK

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS.....	50mm
MAXIMUM SIZE OF DEAD KNOTS.....	30mm
HEARTWOOD.....	Allowed
SAPWOOD.....	Allowed
INSECT HOLES.....	Not Allowed
FILLER.....	Allowed
COLOR VARIATION.....	Allowed
SMALL CRACKS.....	Allowed
ROT.....	Not Allowed

TECHNICAL CRITERIA

ORIGIN.....	Europe
JANKA HARDNESS RATING.....	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION.....	E1
PENTACHLOROPHENOL EMISSION.....	ND
REACTION TO FIRE.....	Dfl s1
THERMAL CONDUCTIVITY.....	0.16 W / mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK



WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET DESIGN PANELS PERIMETER BEVEL

PRODUCT DETAILS

CONSTRUCTION.....	Engineered Wood
SPECIES.....	Oak
WEAR LAYER.....	4mm Oak
BACKING.....	Birch Ply
THICKNESS.....	15mm
WIDTH.....	750mm
LENGTH.....	750mm
PACK SIZE.....	0.56m ²
PLANKS PER PACK.....	1
PLANKS PER PALLET.....	N/A
GRADE.....	Rustic
FINISH.....	Hardwax oil
JOINT TYPE.....	Tongue & Groove
BEVELLED EDGES.....	Only on perimeter joints
FIXING METHOD.....	Stuck down
UNDERFLOOR HEATING.....	Suitable if fully stuck down
TOG RATING.....	1.13



AVAILABLE IN LIMED OAK | ROYAL OAK | AGED OAK

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS.....	50mm
MAXIMUM SIZE OF DEAD KNOTS.....	30mm
HEARTWOOD.....	Allowed
SAPWOOD.....	Allowed
INSECT HOLES.....	Not Allowed
FILLER.....	Allowed
COLOR VARIATION.....	Allowed
SMALL CRACKS.....	Allowed
ROT.....	Not Allowed

TECHNICAL CRITERIA

ORIGIN.....	Europe
JANKA HARDNESS RATING.....	1,360 lbf (6,000N)
FORMALDEHYDE EMISSION.....	E1
PENTACHLOROPHENOL EMISSION.....	ND
REACTION TO FIRE.....	Dfl s1
THERMAL CONDUCTIVITY.....	0.16 W / mK

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK

