WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET WARWICK HAZELNUT OAK DESIGN PANEL


PRODUCT DETAILS

PRODUCT CODE	34-WCK-004
CONSTRUCTION	Natural mineral / resin composite
WEAR LAYER	0.5mm PU coated vinyl
BACKING	Crosslinked microcellular foam
THICKNESS	
WIDTH	600mm
LENGTH	600mm
PACK SIZE	216m²
PLANKS PER PACK	6
FINISH	LiveTouch™
JOINT TYPE	Easiloc
END JOINT TYPE	5G
BEVELLED EDGES	Bevel All 4 Edges
FIXING METHOD	Floated
UNDERFLOOR HEATING	GSuitable
MOISTURE BARRIER	Not Required
PERIMETER EXPANSION	GAP 2-3mm
SUBFLOOR TOLERANCE	<3mm



TECHNICAL CRITERIA

FORMALDEHYDE EMISSION	EI
PENTACHLOROPHENOL EMISSION	Undetected
WEAR RATING	
REACTION TO FIRE	Dfl s1
THERMAL CONDUCTIVITY	0.13W/mK
DIMENSIONAL STABILITY	0.08%
SHRINKAGE RATE 5-35C	0.01%
IMPACT SOUND REDUCTION	19dB



SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR **T**: 02920 888 223 **F**: 02920 881 694 info@woodpeckerflooring.co.uk

