

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET DARTMOUTH SMOKED OAK

PRODUCT DETAILS

PRODUCT CODE	75-DSM-190
CONSTRUCTION	Engineered Wood
SPECIES	Oak
BACKING	Plywood
THICKNESS	15mm
WIDTH	190mm
LENGTH	1900mm
Packs include cut lengths	
PACK SIZE	2.166m ²
PLANKS PER PACK	6
GRADE	Extra Rustic
FINISH	UV Oiled
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if stuck down
TOG RATING	1.13

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	Not Restricted
MAXIMUM SIZE OF DEAD KNOTS	50mm
HEARTWOOD	Allowed
SAPWOOD	Allowed
INSECT HOLES	Not Allowed
FILLER	Allowed
COLOUR VARIATION	Allowed
SMALL CRACKS	Allowed
ROT	Not Allowed



SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK

