

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA SHEET BOURTON NATURAL OAK

### PRODUCT DETAILS

PRODUCT CODE .....	77-BNA-240
CONSTRUCTION .....	Engineered Wood
SPECIES .....	Oak
WEAR LAYER .....	3mm
BACKING .....	Poplar
THICKNESS .....	15mm
WIDTH .....	240mm
LENGTH .....	2200mm
PACK SIZE .....	2.11m <sup>2</sup>
PLANKS PER PACK .....	4
PACKS PER PALLET .....	50
GRADE .....	Prime
FINISH .....	UV Oiled
JOINT TYPE .....	Tongue & Groove
BEVELLED EDGES .....	All 4 Edges
FIXING METHOD .....	Floated, nailed or stuck down
UNDERFLOOR HEATING .....	Suitable if stuck down
TOG RATING .....	1.13

### GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS .....	10mm
MAXIMUM SIZE OF DEAD KNOTS .....	Not Allowed
HEARTWOOD .....	Not Allowed
SAPWOOD .....	Not Allowed
INSECT HOLES .....	Not Allowed
COLOUR VARIATION .....	Limited
SMALL CRACKS .....	Not Allowed
ROT .....	Not Allowed



### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 [info@woodpeckerflooring.co.uk](mailto:info@woodpeckerflooring.co.uk)

[WWW.WOODPECKERFLOORING.CO.UK](http://WWW.WOODPECKERFLOORING.CO.UK)

