

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA SHEET BOURTON NATURAL OAK HERRINGBONE

PRODUCT DETAILS

PRODUCT CODE	77-BNA-090
CONSTRUCTION	Engineered Wood
SPECIES	Oak
WEAR LAYER	3mm
BACKING	Plywood
THICKNESS	15mm
WIDTH	90mm
LENGTH	400mm
PACK SIZE	1.296m ²
PLANKS PER PACK	36
PACKS PER PALLET	50
GRADE	Prime
FINISH	UV Oiled
JOINT TYPE	Tongue & Groove
BEVELLED EDGES	All 4 Edges
FIXING METHOD	Floated, nailed or stuck down
UNDERFLOOR HEATING	Suitable if stuck down
TOG RATING	1.13

GRADING CRITERIA

MAXIMUM SIZE OF SOUND KNOTS	10mm
MAXIMUM SIZE OF DEAD KNOTS	Not Allowed
HEARTWOOD	Not Allowed
SAPWOOD	Not Allowed
INSECT HOLES	Not Allowed
COLOUR VARIATION	Limited
SMALL CRACKS	Not Allowed
ROT	Not Allowed



SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the floor of their choice is still available with the specification shown.

Woodpecker House, 26 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK

